

CHECKLIST FALCON SITE ASSESSMENT

PREPARATION AND

WATERLESS URINAL SITE ASSESSMENT

INSTALLATION **IDENTIFY CRITICAL INFORM ATION** DRAIN LINE PRE PARATION Identify if facility has LEED/Green Expert. Waterfree urinals must be installed on clean Identify current urinal gallons per flush. drain pipes that are free of obstructions and mineral build up. Pre-installation drain line Look for leaking flush valves or other issues cleaning reference sheet is available at www. (e.g., odor). FalconWaterfree.com. Obtain critical measurements to determine the Confirm that copper is not being used for any appropriate Falcon Waterfree® urinal to cover portion of the DWV system associated with the the footprint of the existing urinals and the waterless urinal. correct height for installation. • Drain and lip height of existing urinal. Drain pipes must have proper slope to allow • Width and height of existing urinal. complete drainage of liquid through the piping system after each use. If drain height adjustment is required, assess wall condition to determine need for repairs. INSTALLATION OF URINAL Full weight of the urinal should be supported by the uni-bracket, never on the tall pipe of the **ASSESS DWV SYSTEM** urinal housing. Assess in-wall plumbing to verify code compliance for downhill slope, venting and Install urinal in accordance with manufacturer's DWV material. Waterfree urinals are suitable instructions for optimal performance. Review of installation video at www.FalconWaterfree.com for installation on all DWV except copper. and in-box instructions is highly recommended. Confirm that copper is not being used for any portion of the DWV system associated with ONGOING CUSTODIAL the waterless urinal. CARE OF URINAL **RESEARCH & PROVIDE S AVINGS ANALYSIS PURCHASE THE PROPER SUPPLIES** Research water / sewage rate for facility. Order foam housing cleaner and urinal brush to facilitate easier cleaning. Provide cost savings analysis to a facility manager with mutually agreed upon **ENSURE PROPER MAINTENANCE** assumptions, such as the number of users and operating days per year. Custodians should watch the online maintenance video for training. One sheet custodial aid on the proper care of urinals should be provided to custodial staff for reference and placed in janitorial closets, available at www.FalconWaterfree.com. During cartridge change out-procedure, it is vital to flush the system with 3-5 gallons of water when the

cartridge is removed from the urinal.

instructions.

Prime the new cartridge with water prior to pouring sealant into the cartridge, per cartridge change